



SAFETY DATA SHEET

CRACK REPAIR PART B

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CRACK REPAIR PART A RESIN
PRODUCT CODES:
MANUFACTURER: GALAXY EPOXY, LLC
DIVISION: FLOOR COATING
ADDRESS: 2424 W 14TH STREET
TEMPE AZ 85281
PRODUCT USE: FLOOR COATING
PREPARED BY: GALAXY EPOXY, LLC

CHEMICAL SPILL
EMERGENCY PHONE: 800-255-3924
CHEMTel PHONE:
OTHER CALLS:
FAX PHONE:
CHEMICAL NAME:
CHEMICAL FAMILY:
CHEMICAL FORMULA:



SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION: Oral Toxicity 4 Oral >300+ <=2000mg/kg
Signal Word: WARNING Eye Corrosive 2A Eye irritant: Subcategory 2A, Reversible in 21 days

HAZARD STATEMENTS: H302 Harmful if swallowed
H319 Causes serious eye irritation

PRECAUTIONARY STATEMENTS (PREVENTION): P264 Wash exposed skin thoroughly after handling
P270 Do not eat, drink or smoke when using this product
P280 Wear protective gloves/clothing and eye/face protection.

PRECAUTIONARY STATEMENTS (RESPONSE): P330 Call a POISON CENTER or doctor/physician if you feel unwell
P301 + P312 IF SWALLOWED: Call POISON CENTER or doctor/physician if you feel unwell
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 Get medical advice/attention

PRECAUTIONARY STATEMENTS (DISPOSAL): P501 Dispose of contents/container to hazardous or special waste collection point.

HAZARDS NOT OTHERWISE CLASSIFIED

No specific dangers known, if the regulations/notes for storage and handling are considered

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	WGT%	CAS#
Polyoxypropyleneglycol	70 - 90	9082-00-2
Di-Meethylthio Toluenediamine	20 - 30	Proprietary
Castor Oil	2 - 3	2-3121053-17-6

SECTION 4: FIRST AID MEASURES

Move exposed person to fresh air. If breathing is labored, oxygen should be administered by qualified personnel.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

After contact with skin, wash immediately with plenty of warm, soapy water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.



SAFETY DATA SHEET

CRACK REPAIR PART B

SECTION 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA :

Water, Foam, CO2 or dry powder.

CAUTION:

Heating or fire can release toxic gas.

HAZARDOUS DECOMPOSITION PRODUCTS:

Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, and hydrocarbons.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Promptly isolate the scene by removing all persons from the vicinity of the incident, if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

SECTION 6: ACCIDENTAL RELEASE MEASURES

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7: HANDLING AND STORAGE

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get into eyes.

Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and may be hazardous.

Material is to be stored in accordance with local regulations. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Use appropriate containment to avoid environmental contamination.

Unsuitable containers: Do not store in containers made of copper, copper alloys or galvanized surfaces.



SAFETY DATA SHEET

CRACK REPAIR PART B

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Smell is not an adequate indicator of hazard.
VENTILATION:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
PROTECTIVE GEAR:	<p>In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all time when handling chemical products if a risk assessment indicates this is necessary.</p> <p>Safety eyewear complying with an approved standard should be used when a risk assessment indicate this is necessary to avoid exposure to liquid splashes, mists or dusts.</p> <p>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</p>

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

FORM:	liquid.
ODOR:	Faint
ODOR THRESHOLD:	N/A
COLOR:	As color specified (Naturally Yellowish Amber)
PH VALUE:	N/A
FREEZING POINT:	N/A
BOILING POINT:	N/A
FLASH POINT:	161°C
FLAMMABILITY:	Not flammable
AUTOIGNITION:	N/A
VAPOR DENSITY:	N/A
VISCOSITY:	N/A
SELF-IGNITION TEMPERATURE:	This product is not classified as self-igniting
THERMAL DECOMPOSITION:	No decomposition if handled and stored as prescribed/indicated.
SOLUBILITY IN WATER:	N/A
EVAPORATION RATE:	N/A
% WEIGHT VOLATILE (VOC):	0.00

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable at room temperature. No specific test data related to reactivity is available for this product or its ingredients.
HAZARDOUS REACTIONS:	None known. Stable under normal conditions.



SAFETY DATA SHEET

CRACK REPAIR PART B

SECTION 11: TOXICOLOGICAL INFORMATION

COMPONENT TOXICITY	N/A
ROUTES OF ENTRY	Skin Contact, Eye Contact, Ingestion
TARGET ORGANS	Eyes
EFFECTS OF OVEREXPOSURE	N/A
CARCINOGENICITY	None

SECTION 12: ECOLOGICAL INFORMATION

Only component information is listed, if any. No testing has been performed on this mixture as it relates to ecological impact.

SECTION 13: DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized by using excess product in an alternate, beneficial application wherever possible. Empty containers may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers

SECTION 14: TRANSPORT INFORMATION

LAND TRANSPORT

US DOT

Not classified as a dangerous good under transport regulations

SEA TRANSPORT

IMDG

Not classified as a dangerous good under transport regulations

AIR TRANSPORT

IATA/ICAO

Not classified as a dangerous good under transport regulations

FURTHER REGULATIONS

DOT:

This product is regulated if the amount in a single receptacle exceeds the Reportable Quantity (RQ). Please refer to Section 15 of this SDS for the RQ for this product.



SAFETY DATA SHEET

CRACK REPAIR PART B

SECTION 15: REGULATORY INFORMATION

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30, unless listed below:

-None

This product contains the following substance(s), which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372:

-None

SECTION 16: OTHER INFORMATION

DISCLAIMER/STATEMENT OF LIABILITY:

The data in this Safety Data Sheet is offered for your consideration, investigation and verification. The data is presented in good faith and was obtained from sources GALAXY EPOXY, LLC believes to be reliable. GALAXY EPOXY, LLC however, makes no representation as to the completeness or accuracy. GALAXY EPOXY, LLC makes no warranty, express or implied, with respect to the data contained herein. GALAXY EPOXY, LLC cannot anticipate all conditions under which this data and the product may be used. The conditions of handling, storage, use, and disposal of the product are beyond GALAXY EPOXY, LLC control. Thus, we expressly disclaim responsibility or liability for any loss, damage or expense arising out of reliance on the information contained herein. You are advised to make your own determination as to safety, suitability and appropriate manner of handling, storage, use and disposal.